

## FILLMATIC S

### PRODUCT DESCRIPTION

The Fillmatic S is a counter pressure filler, with which CO<sub>2</sub>-containing beverages can be filled under counter pressure of up to 3bar. In order to be able to control the filling process better, the bottles are illuminated with an LED lamp. The filling process is automatically stopped by the control system when the target value is reached. All process-relevant parameters can be set via the control system, which guarantees reliable reproducibility of all parameters during the entire filling process.

It can be used to fill glass bottles (0.25l to 0.75l), siphons and barrels (5l); PET bottles are also available on request.

The filling speed can be adjusted continuously from 0.5 to 2l/min by means of a throttle.

Approximately 150 bottles of 0.5l can be filled per hour.



### PRODUCT DATA

DIMENSIONS H/W/D: 1140/210/340MM

WEIGHT: 29KG

FILLING SPEED: 0,5 TO 2L/MIN

CO<sub>2</sub> OPERATING PRESSURE: MAX. 3BAR

ELECTRICAL DATA: 240V 2A

### SCOPE OF DELIVERY

ONE BOTTLE HOLDER AS DESIRED

CONNECTION ACCESSORIES FOR KEG TAP HEAD OR FERMENTATION TANK

### AVAILABLE ACCESSORIES

CAN FILLING HEAD

(SAMPLE CAN IS REQUIRED)

FILLING HEAD FOR GLASSES

(SAMPLE GLASS IS REQUIRED)

### PRICE

PLUS VAT, PACKAGING AND SHIPPING