

PRODUCT DESCRIPTION

The Fillmatic S is a counter pressure filler, with which CO₂-containing beverages can be filled under counter pressure of up to 3bar. In order to be able to control the filling process better, the bottles are illuminated with an LED lamp. The filling process is automatically stopped by the control system when the target value is reached. All process-relevant parameters can be set via the control system, which guarantees reliable reproducibility of all parameters during the entire filling process.

It can be used to fill glass bottles (0.25l to 0.75l), siphons and barrels (5l); PET bottles are also available on request.
The filling speed can be adjusted continuously from 0.5 to 2l/min by means of a throttle.
Approximately 150 bottles of 0.5l each can be filled per hour.



PRODUCT DATA

DIMENSIONS H/W/D: 1140/210/340MM
WEIGHT: 29KG
FILLING SPEED: 0,5 TO 2L/MIN
CO₂ OPERATING PRESSURE: MAX. 3BAR
ELECTRICAL DATA: 240V 2A

SCOPE OF DELIVERY

ONE BOTTLE HOLDER AS DESIRED

AVAILABLE ACCESSORIES

CAN FILLING HEAD (SAMPLE CAN IS REQUIRED)
FILLING HEAD FOR GLASSES (SAMPLE GLASS IS REQUIRED)