

HOP TAMPERS

FH MASCHINEN UND BRAUMANUFAKTUR WERK II GMBH

WALBURGER STR. 35

+49 (0) 5604 93 699 15

MAIL INFO@WERK-2.EU

37247 GROSSALMERODE

+49 (0) 171 743 66 19

WEB WWW.WERK-2.EU

BRAUMANUFAKTUR
WERK GmbH

PRODUCT DESCRIPTION

With our hop tamper it is possible to upgrade beer in KEG barrels with hop cones or pellets. The cylinder is first filled with hops, then closed and attached to the tapping head of the keg. Now the beer from the keg is pressed through a valve into the hop tamper. After cold hopping, the beer is forced back into the keg with carbon dioxide.

SAFETY NOTE

The safety valve (1.5bar) must not be manipulated! The CO₂ and beer check valves in the keg coupler must be removed. WERK II GmbH assumes no liability for these safety-relevant measures.



PRODUCT DATA

DIMENSIONS ø/H: 160/550MM
WEIGHT: 10KG
CO₂ OPERATING PRESSURE: MAX. 1.5BAR
CONNECTION TAP HEAD: 5/8"
HOP QUANTITY: MAX. 250G PELLETS

SCOPE OF DELIVERY

HOSES AND BALL VALVES WITH SAFETY VALVE (DEFAULT 1.5BAR)